

Flow-Max Stainless Steel Filter Housings

Stainless steel filter housings with easy, safe and secure band-clamp lid closure.



Flow-Max® Commercial Quality Multi-Cartridge Stainless Steel Filter Housings (316SS and 304SS)

MODEL NO. (316SS)	MODEL NO. (304SS)	ROUND	MAX. FLOW RATE (GPM) PLEATED	MAX. FLOW RATE (GPM) DEPTH	PIPE SIZE	DRAIN SIZE (NPT)	NO. OF STANDARD CARTRIDGES	CARTRIDGE OPTIONS (LENGTHS)
N/A	FM4X1-1-304	4	25	25	1" NPT	1/2"	4	9-3/4" - 10"
FM5X1	FM5X1-304	5	30	25	2" NPT	1/2"	5	9-3/4" - 10"
FM4X2	FM4X2-304	4	60	40	2" NPT	1/2"	4	20"
FM4X3	FM4X3-304	4	90	60	2" NPT	1/2"	4	29-1/4" or 30"
FM4X4	FM4X4-304	4	120	80	2" NPT	1/2"	4	40"
FM5X4	FM5X4-304	5	150	100	2" NPT	1/2"	5	40"
FM12X3	FM12X3-304	12	250	180	3" flange	1/2"	12	29-1/4" or 30"
FM12X4	FM12X4-304	12	300	240	3" flange	1/2"	12	40"
FM22X3	FM22X3-304	22	500	330	4" flange	1/2"	22	29-1/4" or 30"
FM22X4	FM22X4-304	22	600	440	4" flange	1/2"	22	40"

Flow-Max® Premium Series Housings With Mounting Legs And Pressure Gauges (316SS)

MODEL NO.	ROUND	MAX. FLOW RATE (GPM) PLEATED	MAX. FLOW RATE (GPM) DEPTH	PIPE SIZE	DRAIN SIZE (NPT)	NO. OF STANDARD CARTRIDGES	CARTRIDGE OPTIONS (LENGTHS)
FMPS4X2	4	60	40	2" NPT	1/2"	4	20"
FMPS5X3	5	120	75	2" NPT	1/2"	5	29-1/4" or 30"
FMPS5X4	5	150	100	2" NPT	1/2"	5	40"
FMPS7X4	7	200	140	2" NPT	1/2"	7	40"

Note: Flow rates shown above are for guidelines only. Actual flow rates are based on cartridge type, micron rating, solids content and a number of other factors.

Stainless Steel Filter Housings – Tabs

MODEL NO.	DESCRIPTION
TABS	MOUNTING TABS FOR 457 ROUND